



SYNCH. BUENO  
KEEP UP WITH THE TIME SERVER

# NTP+IRIG-B Time Server

SY-2C-NTP04B



## Introduction

The SY-2C-NTP04B(4 port of NTP/SNTP output) Network IRIG-B Time server provides a high precision time directly to TCP/IP networks using NTP(Network Time Protocol) and IRIG-B timing receiver. It synchronizes time of any NTP clients running on remote PC' s. It supports both NTP and SNTP clients for more of current popular operating systems including: Microsoft Windows 95/98/Me/NT/2K/XP, Linux, Free BSD, IBM AIX and other UNIX family systems. It can synchronize simultaneously thousands of servers, workstations and routers.

## Features

The SY-2C-NTP04B is high quality professional time server for computing, telecom, military, power grid, traffic systems and other science purposes. It has been manufactured with no mechanical parts as coolers or hard disk. All cooling system has been resolved on natural air circulation outgoing via metal case of unit.

## Technology

NTP : supports all versions of NTP, SNTP including latest release 4.1.1 supporting modes: CLIENT,SERVER, BROADCAST, MULTICAST. Authentication: MD5 with manual/automatic key generation.

SNTP : supports all versions of Simple Network Time Protocol

OS Supports :Windows 95/98/Me/2K/XP/WIN7/CE, OS/2, VAX-11/785 v4.3, HPUX, SunOS, Solaris, MIPS Ultrix, ALPHA OSF/1, SGI IRIX, A/UX, AIX, Sinix, BSD, Linux, Dell SVR4, SCO Unixware, CISCO products.

[www.synchbueno.com](http://www.synchbueno.com)

IRIG-B: 4 of BNC ports(IRIG-B DC)

**The following outputs are only for options:**

RS-485: 1 channels(serial code) or more,terminal block port

RS-232:1 channels(block terminal) or more. 1 channel of DB9 connector

PPS: 2 channels 1 PPS(TTL/ active optical isolation and passive) PPM: 1 channel 1PPM

Support dual redundant power supplies(For Optional)

**Other technical Specs:**

LAN : 4x10/100 Based Tx: RJ-45 connector IEEE 802.3 - shielded data line

Chipset : Motorola receiver (8) channel with RAIM

Antenna: BNC1.5GHz / 8m + active converter (IP65 to UTP Cat5. cable 200m. (max.500m),

Receiver : input frequency 1575.42MHz (L1).

Input : 110-240V AC/DC, DC48V,DC24V,DC12V

Fuse : 1 electronic

Outputs : +5V / 5A, +12V / 0.6A, -12V / 0.5A Total Load : Less than 15 Watt

NTP Accuracy: 1ms after synchronization of first 1 hour better than  $\pm 1$   $\mu$ sec during the first hour of operation

IRIG-B Accuracy: 1us.

Housing : Metal desktop case,2U

Front Panel: 86mm high / 483mm wide

Protection : rating IP20

LCD Display: 6 character+8 character .Can display local date & time ,longitude, latitude,altitude,time zone code,satellite number locked.

Temperature : -20~ 75°C. Ambient temperature supported.

Storage: -40~ 125°C

Humidity: 85% max

Housing Color: Grey

GPS Antenna Cable: 30 meters wire with GPS antenna

Warranty: 5 Years